

Actro 5D with Silent System, optionally with Push to open Silent

Full extension runner Actro 5D L (40 kg) with Silent System, compatible with Push to open Silent, 600 mm, left and right



- Drawer runner for combining with wooden drawer
- Full extension runner with integrated tilt adjustment and radial adjustment
- Slide on installation with 2D catches for tool-less height and side adjustment
- Optional: depth adjustment
- Integrated
- Adjustments all toolless: height adjustment up to + 3 mm, side adjustment up to +/- 1.5 mm, tilt adjustment up to + 4 mm and radial adjustment up to +/- 1.5 mm and depth adjustment up to +/- 2 mm
- Suitable for drawers with a side profile thickness of up to 16 mm
- Optional: Push to open Silent opening system
- Optional: pull-out shelf support / pull-out shelf locating catch
- Load capacity to EN 15338, Level 3
- Galvanised steel
- Advice:
- Catch must be ordered separately



shop.hettich.com/ca_EN/p/9318291

Actro 5D with Silent System, optionally with Push to open Silent

Article
Number 9318291

- Full extension runner Actro 5D L (40 kg) with Silent System, compatible with Push to open Silent, 600 mm, left and right

FEATURE	VALUE
Load class	L (40 kg)
Nominal length	600
Mounting side	left and right
User friendly features	Silent System, compatible with Push to open Silent
Drawer length SKL	590 mm
Load capacity kg	40
Installed width EB	23
Hole spacing b1	256
Type of runner	Concealed runner
Runner type	Concealed runner
Type of drawer runner	Full extension runner
Load class	40 kg
Minimum cabinet body depth KT	603
Type of installation	slide on installation
Installed width (side profile thickness)	EB 21 (drawer side profile thickness \leq 16mm)
Components	Drawer runners
Previous order no.	9268684
Order no.	9318291
PU	1

Safety instructions

	Follow instructions
	Warning against pointed and sharp objects
	Warning of pinching and crushing edges. Do not reach into open door gaps or fitting openings.
	Not suitable for children under 3 years. Risk of swallowing due to small parts.
	Caution! Ensure a suitable choice of material.
	Attention shipping packaging! Fittings may fall out if opened carelessly.
	Attention! Only suitable for indoor use and the usual climatic conditions there